



# SM07S3

## Rear Vision System

System includes (1) C003 Camera

*Call for Big Savings 574-807-6004*

Engineered to meet the commercial demands and still be VERY budget minded. This 7" LCD Monitor has a clear, crisp view in our durable housing. The monitor supports up to (3) Verity cameras. The SM07S3 includes our ADD21U "S" mount and (1) 65' camera cable. Ideal for limited installation space!

### MONITOR SPECIFICATIONS (Part #MK07S)

- (Monitor part #MK07S)
- Screen size: 7-inch digital screen (16:9)
- High Resolution: 1024 x 600 Pixel (RGB)
- System: PAL/NTSC Auto Select
- Contrast: 400:1
- Brightness: 300 cd/m2
- Power supply: DC 12V~24V with reverse polarity protection
- Operation temperature: -30°~80°C
- Storage temperature: -20°~70°C
- Monitor view angle: Horz. L (70) R (70) Vert. UP (50) DOWN (70)
- 3 AV with shrink tube labeled trigger wires,
- Auto blue screen if no signal on the activated channel.
- Size: 141 x 103 x 25 mm.
- Weight: 418 g.



Features: Removable HD sunshade, LCD screen, LED blue light buttons, high-quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons: reversing image delay time 0~10s, Mirror/Normal image, plus horizontal flip, multi-language.

### CAMERA SPECIFICATIONS (Part #C003)

#### CAMERA SPECIFICATIONS

(Camera Part #C003)

- Horizontal Resolution: 600 TV Lines
- TV System: NTSC
- Image Type: 1/3 Inch Color CCD Sharp® (or equivalent)
- Effective Pixel: 510 x 492
- Illumination: 0 Lux (built-in 8 high output IR LEDs for night vision)
- Aluminum Housing
- Waterproof: IP67
- Power Supply: DC 12V (powered from the monitor)
- Operating Temperature: -20°C ~ +75°C
- Viewing Angle: 150-degree diagonal / 90-degrees horizontal.



574-807-6002

[www.veritysafe.com](http://www.veritysafe.com)

Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

A division of Component Solution Services, LLC.

Woman-Owned

Est. 2002

Subject to change without notice